



The ultimate 4G-LTE-peripheral device for any router

bintec 4Ge-LE

- Easy option to equip new / existing routers with LTE (4G)
- Compatible to nearly all routers. Not producer-bound
- No management necessary Setup in the connected router
- Small and discreet you nearly don't see it
- Power supply by PoE or PSU
- Wall mounting for easy and secure fixing





bintec 4Ge-LE

The ultimate 4G-LTE-peripheral device for any router

The bintec 4Ge is an innovative 4G problem solver, which allows to equip existing IT networks with 4G. The installation outside of server racks leads to significant improved 4G connections.

The innovative LTE (4G) problem solver

The bintec 4Ge is an affordable extension unit that allows owners of existing router infrastructures to retrofit their systems with LTE (4G) connectivity. The 4Ge accomplishes this by simply connecting to the router through a 10/100/1000 Mbps Ethernet port. Once connected, all further configurations can be easily carried out on the router itself. Thanks to the use of standard protocols, the 4Ge is compatible with most routers regardless of the manufacturer. The device gets its power either by means of the included Power over Ethernet injector or an external power supply. The housing includes an integrated wall mount allowing quick and easy installation. The 4Ge also comes equipped with a Kensington slot so you can secure your hardware against theft.

Applications and benefits of the bintec 4GE at a glance

Enterprise routers are usually located inside the server room. But that's a place where mobile data coverage is rarely available - and if it is, the signal is normally not strong enough for broadband speeds. The poor signal can result in data transfers slowing to a crawl. To ensure this does not happen to you, simply install the bintec 4GE outside the server room at the location with the best 4G signal. The bintec 4Ge then establishes a high-speed LTE (4G) connection that is available on the company's Ethernet network.

- The easy way to retrofit existing routers with LTE.
- No separate management interface required all settings can be made directly on the router.
- Thanks to the use of standard protocols which are compatible with most routers, no vendor lock-in.
- Power is obtained from PoE or a power supply.
- Small and unobtrusive for inconspicuous installations in business settings.
- Wall-mountable for simple and secure installation.

Variants

bintec 4GE-LE (5530000119)	LTE (4G)/UMTS (3G) extension device for router; 1x Gbit Eth; Simcard slot;
	Wallmounting; PoE Injector inclusive

Features

Service

Warranty

2 year manufacturer warranty

bintec elmeg GmbH - Suedwestpark 94 - 90449 Nuremberg - Germany Phone: +49 - 911 9673-0 - Telefax: +49 - 911 688 07 25 E-Mail: info@bintec-elmeg.com - www.bintec-elmeg.com bintec 4Ge-LE 06.10.2014 Subject to technical alterations



LTE(4G) / UMTS(3G)

Supported standards	Support of LTE - 4G (download rate up to 100 Mbps, upload rate up to to 50 Mbps), UMTS 3.5G (HSPA+), GPRS, Edge and GSM
LTE(4G) bands	800/900/1800/2100/2600 MHz
UMTS (3.5G) / EDGE - GPRS (2G) bands	850/900/1800/1900/2100 MHz

Interfaces	
Ethernet	1x 10/100/1000 MBit/s Ethernet
SIM card slot	1x SIM Card Slot (Mini SIM 2ff) accessible from outside
External LTE-UMTS antenna connectors	Two SMA antenna connectors for external LTE (4G)-UMTS (3G)- antenna
Power connection	1x for external Powersupply

Hardware	
Power consumption	approx. 5 Watt
Housing	Plastic case incl. preparation for Kensington lock and wall mounting
Dimension	Approx. 145 mm x 50 mm x 160 mm (W x H x D)
Weight	0,3 kg
Reset button	Restart or reset to factory state possible
Status LEDs	Power, Status, 2x Ethernet, LAN, WLAN
Wall mounting	Integrated in housing
Environment	Temperature range: Operational 0°C to 45°C; storage -25°C to 70°C; Max. rel. humidity 5 - 90% (non condensing)
Power supply (not included in the scope of delivery)	External power supply 110-240V / 12 V DC, 1.0 A, with energy efficient switching controler;
Fan	Fanless design therefor high MTBF
Desktop operation	Possible, rubber pad included
PoE	Power over Ethernet IEEE 802.3af client. RJ45 Gbit Ethernet connector
PoE class	max. 12,95W

Content of Delivery	
Quick start guide	Quick Installation Guide in German and English
Installation Poster	Guide for the Installation
Ethernet cable	1x Ethernet cable, 2m
РоЕ	1x PoE Injector + power cable
LTE/ UMTS antenna	Two LTE/ UMTS 2dBi quad-band omni-directional antennas

bintec elmeg GmbH - Suedwestpark 94 - 90449 Nuremberg - Germany Phone: +49 - 911 9673-0 - Telefax: +49 - 911 688 07 25 E-Mail: info@bintec-elmeg.com - www.bintec-elmeg.com bintec 4Ge-LE 06.10.2014 Subject to technical alterations



Content of Delivery

Screws and rawlplug

For wall-mounting

Accessoires

Add-ons	
Wall mounting Wx003n/4n/4Ge-LE (5500001278)	Wall and ceiling mounting (spare part) for W1001n, W1003n, W2003n, W2003n, W2003n-ext, W2004n, 4Ge-LE
ANT-4G-LTE-Cross-Pol (5500001467)	Cross polarised 8 dbi Mimo multi-band LTE(4G)-UMTS(3G) antenna incl. Mounting kit and 5 m cable for outdoor usage, SMA connector for RS353j-4G, RS232j-4G, RS120wu, RS230au+, RS232bu+
ANT-Omni-3G/4G-UMTS/LTE (550000853)	Omni-directional multi-band GSM-3G (UMTS) antenna incl. mounting kit and 5 m cable for outdoor usage, SMA connector for RS120wu, RS230au+, RS232bu+, RS232j-4G, RS353j-4G